



Product data sheet

Power tools for trade & industry

Rotation Laser

PRO GRL18V-4-34CVG



Robust rotary laser with intuitive dial-in slope adjustment

The most important data

Working range with receiver	400 m (diameter)
Accuracy	± 3.0 mm at 30 m vertical, ± 1.5 mm at 30 m horizontal
Self-levelling range	± 15% (± 8.5 °)

Part Number 0 601 061 H01

Technical data

Technical data

Battery voltage	18.0 V
Laser diode	500 – 540 nm, < 1 mW
Operating temperature	-10 – 50 °C
Storage temperature	-20 – 50 °C
Laser class	2
Working range with receiver	400 m (diameter)
Accuracy	± 3.0 mm at 30 m vertical, ± 1.5 mm at 30 m horizontal
Self-levelling range	± 15% (± 8.5 °)
Dust and splash protection	IP66
Rotation speed	150/300/600 min ⁻¹
Power supply	4 x 1.5 V LR14 (C), 18 V Li-Ion battery
Tripod thread	2 x 5/8"
Weight, approx.	3.1 kg
Colour of laser line	Green
Color of plumb points	Green
Projection	1 x 360° line
Compatible laser receivers	LR 45
Packaging dimensions (width x length x height)	360 x 440 x 390 mm

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Intuitive dial-in slope with a bi-colour LED keypad to save time and ensure clear visibility from a distance
- IP66 rating and 1.5 m tripod tip-over resistance for peace of mind on tough jobsites
- Powered by 18V LI-batteries or alkaline C-cells for uninterrupted work



You can find more information about the deviations in the following link: <https://www.bosch-professional.com/gb/en/wac/>

